

[illegible]

FOR UNITED STATES LETTERS PATENT

• • • •

TO ALL WHOM IT MAY CONCERN:

1

STUD MARKING DEVICE

5

BACKGROUND OF THE INVENTION

Field of the Invention

10

The present invention relates to a stud marker and more particularly pertains to a new stud marking device for easily and quickly marking locations of studs.

15 Description of the Prior Art

20

The use of a stud marker is known in the prior art. More specifically, a stud marker heretofore devised and utilized are known to consist basically of familiar, expected and obvious structural configurations, notwithstanding the myriad of designs encompassed by the crowded prior art which have been developed for the fulfillment of countless objectives and requirements.

25

Known prior art includes U.S. Patent No. 3,577,918; U.S. Patent No. 5,749,522; U.S. Patent No. Des. 383,399; U.S. Patent No. 4,989,342; U.S. Patent No. 3,835,543; and U.S. Patent No. 3,616,541.

While these devices fulfill their respective, particular objectives and requirements, the aforementioned patents do not disclose a new stud marking device. The inventive device includes a handle having a tubular base member having a pair of prong-like members extending outwardly from a bottom thereof, and further having three telescopic members slidably and lockingly extended within one another, and further includes a wheel being of many different sizes and being rotatably mounted to the prong-like members. As a first embodiment, the wheel has a bore radially extended through the circumference with a marker being threaded in the bore and having a marking end which extends outwardly beyond the circumference. As a second embodiment, the base member has an extended portion with a keypad member mounted thereto, an LCD display and driver disposed therein, a microcontroller having read only memory disposed in the extended portion, a spring-loaded marker disposed in a bottom of the extended portion, and a plurality of marker-triggering members securely and spacedly disposed on one side of the wheel for triggering the release of the spring-loaded marker to mark the locations of the studs.

In these respects, the stud marking device according to the present invention substantially departs from the conventional concepts and designs of the prior art, and in so doing provides an apparatus primarily developed for the purpose of easily and quickly marking locations of studs.

SUMMARY OF THE INVENTION

In view of the foregoing disadvantages inherent in the known types of a stud marker now present in the prior art, the present invention provides a new stud marking device construction wherein

the same can be utilized for easily and quickly marking locations of studs.

5 The general purpose of the present invention, which will be described subsequently in greater detail, is to provide a new stud marking device which has many of the advantages of the stud marker mentioned heretofore and many novel features that result in a new stud marking device which is not anticipated, rendered obvious, suggested, or even implied by any of the prior art a stud
10 marker, either alone or in any combination thereof.

To attain this, the present invention generally comprises includes a handle having a tubular base member having a pair of prong-like members extending outwardly from a bottom thereof, and
15 further having three telescopic members slidably and lockingly extended within one another, and further includes a wheel being of many different sizes and being rotatably mounted to the prong-like members. As a first embodiment, the wheel has a bore radially extended through the circumference with a marker being threaded in
20 the bore and having a marking end which extends outwardly beyond the circumference. As a second embodiment, the base member has an extended portion with a keypad member mounted thereto, an LCD display and driver disposed therein, a microcontroller having read only memory disposed in the extended portion, a spring-loaded
25 marker disposed in a bottom of the extended portion, and a plurality of marker-triggering members securely and spacedly disposed on one side of the wheel for triggering the release of the spring-loaded marker to mark the locations of the studs.

30 There has thus been outlined, rather broadly, the more important features of the invention in order that the detailed

description thereof that follows may be better understood, and in order that the present contribution to the art may be better appreciated. There are additional features of the invention that will be described hereinafter and which will form the subject matter of the claims appended hereto.

In this respect, before explaining at least one embodiment of the invention in detail, it is to be understood that the invention is not limited in its application to the details of construction and to the arrangements of the components set forth in the following description or illustrated in the drawings. The invention is capable of other embodiments and of being practiced and carried out in various ways. Also, it is to be understood that the phraseology and terminology employed herein are for the purpose of description and should not be regarded as limiting.

As such, those skilled in the art will appreciate that the conception, upon which this disclosure is based, may readily be utilized as a basis for the designing of other structures, methods and systems for carrying out the several purposes of the present invention. It is important, therefore, that the claims be regarded as including such equivalent constructions insofar as they do not depart from the spirit and scope of the present invention.

Further, the purpose of the foregoing abstract is to enable the U.S. Patent and Trademark Office and the public generally, and especially the scientists, engineers and practitioners in the art who are not familiar with patent or legal terms or phraseology, to determine quickly from a cursory inspection the nature and essence of the technical disclosure of the application. The abstract is neither intended to define the invention of the application, which is

measured by the claims, nor is it intended to be limiting as to the scope of the invention in any way.

5 It is therefore an object of the present invention to provide a new stud marking device which has many of the advantages of the stud marker mentioned heretofore and many novel features that result in a new stud marking device which is not anticipated, rendered obvious, suggested, or even implied by any of the prior art a stud marker, either alone or in any combination thereof.

10 It is another object of the present invention to provide a new stud marking device which may be easily and efficiently manufactured and marketed.

15 It is a further object of the present invention to provide a new stud marking device which is of a durable and reliable construction.

20 An even further object of the present invention is to provide a new stud marking device which is susceptible of a low cost of manufacture with regard to both materials and labor, and which accordingly is then susceptible of low prices of sale to the consuming public, thereby making such stud marking device economically available to the buying public.

25 Still yet another object of the present invention is to provide a new stud marking device which provides in the apparatuses and methods of the prior art some of the advantages thereof, while simultaneously overcoming some of the disadvantages normally associated therewith.

30

Still another object of the present invention is to provide a new stud marking device for easily and quickly marking locations of studs.

5 Yet another object of the present invention is to provide a new stud marking device which includes ~~includes~~ a handle having a tubular base member having a pair of prong-like members extending outwardly from a bottom thereof, and further having three telescopic members slidably and lockingly extended within one
10 another, and further includes a wheel being of many different sizes and being rotatably mounted to the prong-like members. As a first embodiment, the wheel has a bore radially extended through the circumference with a marker being threaded in the bore and having a marking end which extends outwardly beyond the circumference.
15 As a second embodiment, the base member has an extended portion with a keypad member mounted thereto, an LCD display and driver disposed therein, a microcontroller having read only memory disposed in the extended portion, a spring-loaded marker disposed in a bottom of the extended portion, and a plurality of marker-
20 triggering members securely and spacedly disposed on one side of the wheel for triggering the release of the spring-loaded marker to mark the locations of the studs.

Still yet another object of the present invention is to provide
25 a new stud marking device that provides accurate and pain-free measurements of stud locations.

Even still another object of the present invention is to provide a new stud marking device that substantially saves times
30 and is efficient.

These together with other objects of the invention, along with the various features of novelty which characterize the invention, are pointed out with particularity in the claims annexed to and forming a part of this disclosure. For a better understanding of the invention, its operating advantages and the specific objects attained by its uses, reference should be made to the accompanying drawings and descriptive matter in which there are illustrated preferred embodiments of the invention.

10 BRIEF DESCRIPTION OF THE DRAWINGS

The invention will be better understood and objects other than those set forth above will become apparent when consideration is given to the following detailed description thereof. Such description makes reference to the annexed drawings wherein:

Figure 1 is a perspective view of a new stud marking device according to the present invention.

Figure 2 is a side elevational view of the wheel of the present invention.

Figure 3 is a side elevational view of the various wheels of the present invention.

Figure 4 is an exploded detailed perspective view of prong-like members and the wheel of the present invention.

Figure 5 is a side elevational view of the second embodiment of the present invention.

Figure 6 is an end elevational view of the second embodiment of the present invention.

Figure 7 is a schematic diagram of the second embodiment of the present invention.

5 DESCRIPTION OF THE PREFERRED EMBODIMENT

With reference now to the drawings, and in particular to Figures 1 through 7 thereof, a new stud marking device embodying the principles and concepts of the present invention and generally
10 designated by the reference numeral 10 will be described.

As best illustrated in Figures 1 through 7, the stud marking device 10 generally comprises a handle 11 including a tubular base member 12 having a pair of prong-like members 14,15 spaced apart
15 and integrally extending from a bottom end thereof, and further including a plurality of telescopic members slidably disposed within one another including the tubular base member 12. The telescopic members includes a first tubular member 20 having a plurality of holes 21 spaced therealong and extending through a
20 wall thereof with the first tubular member 20 being slidably and lockingly extended in the base member 12 with a fastening member 13, and further includes a second tubular member 24 also having a plurality of holes 23 spaced therealong and extending through a wall thereof with the second tubular member 24 being slidably and
25 lockingly extended in the first tubular member 20 with another fastening member 22, and also includes a third elongate member 27 having a hand-hold member 29 securely and conventionally disposed at an end thereof with the third elongate member 27 being slidably and lockingly extended in the second tubular member 24
30 with yet another fastening member 28. The base member 12 further

includes a pair of slots 16,17 each of which extends in a bottom end of a respective one of the prong-like members 14,15.

A means for marking stud locations includes a wheel 30 rotatably mounted to the base member 12 and being extended
5 between the prong-like members 14,15, and further includes an axle member 32 securely and centrally and conventionally attached to either side of the wheel 30 and being adapted to being removeably retained in the slots 16,17 in the base member 12.

As a first embodiment, the wheel 30 includes a bore 31
10 extending in a circumference thereof, and the means for marking stud locations also includes a marker 33 threaded in the bore 31 and having a marking end which extends slightly outwardly beyond the circumference of the wheel 30 for marking a stud location upon a surface.

As a second embodiment, the base member 12 includes an
15 extended portion 40 integrally extending outwardly and angled from one of the prong-like members 14,15 and including a housing. The means for marking stud locations includes a keypad member 41 securely and conventionally mounted to the extended portion 40 for
20 selecting a desired location of a stud upon a surface, an LCD display 42 conventionally disposed in the extended portion 40 and readable by a user, a microcontroller 43 including read only memory and being conventionally disposed within the extended portion and being conventionally connected to the LCD display 42
25 and to the keypad member 41, a spring-loaded marker 44 which is biasedly-disposed in a bottom end of the extended portion 40 for marking stud locations, and a plurality of marker-triggering members 45 spacedly and conventionally disposed or welded upon one side of the wheel 30 for triggering the microcontroller 43
30 which releases the spring-loaded marker 44 to extend outwardly

beyond the circumference of the wheel 30 for marking a surface. The marker-triggering members 45 are essentially rib-like members extending radially of the wheel 30 and being spaced approximately one inch apart as measured along the circumference of the wheel 30. The means for marking stud locations further includes an LCD driver conventionally disposed within the extended portion 40 and connected to the microcontroller 43 which further includes an IR transmitter and IR receiver.

In use, the user can extend the handle 11 up to 55 inches as desired by the user and either select the size of the wheel 30 needed to mark the locations of the studs on a particular surface, or key in the desired locations of the studs in the keypad member 41, and when the wheel 30 reaches the desired locations, the marker-triggering members 45 will trigger the microcontroller which will release the spring-loaded marker 44 which will mark the location on the surface.

As to a further discussion of the manner of usage and operation of the present invention, the same should be apparent from the above description. Accordingly, no further discussion relating to the manner of usage and operation will be provided.

With respect to the above description then, it is to be realized that the optimum dimensional relationships for the parts of the invention, to include variations in size, materials, shape, form, function and manner of operation, assembly and use, are deemed readily apparent and obvious to one skilled in the art, and all equivalent relationships to those illustrated in the drawings and described in the specification are intended to be encompassed by the present invention.

Therefore, the foregoing is considered as illustrative only of the principles of the invention. Further, since numerous modifications and changes will readily occur to those skilled in the art, it is not desired to limit the invention to the exact construction and operation shown and described, and accordingly, all suitable
5 modifications and equivalents may be resorted to, falling within the scope of the invention.

0040500-010700

18